

“Heritage Series II”

Custom Paint Grade Garage Doors

Standard Specifications

Base Door

- 1” Hem/Fir core, mechanically assembled, with machined profiled “Shiplap” joints.
- ¼” marine grade Meranti plywood skins both sides, adhered with staples and waterproof adhesive.
- Full cavity semi-rigid fiberglass insulation.
- Preservative prime painted finish to all surfaces unless specified otherwise.
- Base door thickness, 1 ½”. Overall finished door thickness, 2 1/8”.

Exterior Overlay

- ¼” marine grade Meranti plywood. (included in base door)
- Preservative prime painted finish.
- Optional paint grade Tongue and groove Hemlock overlay available at an extra charge.

Exterior Trim Out

- 5/8” x 5 ½” precision machined Hemlock moulding. (Smart Board moulding also available)
- Adhered with premium construction adhesive and brad nailed to core.
- Preservative prime painted finish.

Glazing

- 3mil clear glass with Hem/Fir grilles standard.
- ½” thermal sealed units available at an extra charge.
- Textured, tempered, and tinted glass also available.
- Simulated Divided Lite glazing available at an extra charge.
- True Divided Lite glazing available at an extra charge.

Hardware (If included)

- 2” heavy gauge track with 15” curve radius, 12” radius also available.
- Low headroom configuration track sets are also available.
- Commercial quality hinges, rollers and hardware.
- Heavy duty torsion springs.

Weather strip kits (If included)

- Arctic grade u-shaped bottom weather strip with rigid P.V.C retainer.
- Wood with vinyl insert weather strip also available.

Visit us @ www.equaldoor.com